



## 0190011\_01 Dimmer - 5-150W - Trailing Edge - 2-way

- Trailing edge dimming
- Overheating and overload protection
- Minimal brightness setable

Easily control the brightness of your lights and create the perfect light for every occasion with the high-power dimmer.

The dimmer uses trailing-edge to dim and includes a trim pot which allows the adjustment to a lower dimming level.

Furthermore, the dimmer is protected against overheating and overloading and includes a soft start, which automatically lowers the inrush power to reduce insertion loss.

The dimmer comes with different knob adapters, this makes sure that the dimmer is compatible with most covers and knobs in Europe. The built-in depth of the dimmer is 24 mm.

**LED's light**

### General

Brand	LED's light
Collection	Functional
PLC Status	Phase out
Warranty	2-Year

### Electrical

Power consumption	150 W
Input voltage.	220 — 240 V
Voltage type	AC

Input frequency	50 Hz
Power factor	0.95
Input current.	650 — 650 mA
Safety class	II
Type of dimming	Trailing-edge

## Performance

IP Rating	IP20
Operating Temperature	0 — 45 °C
Max. load LED (VA)	150 VA
Max. load INC/HAL (W)	300 W

## Mechanical

Article length	70 mm
Article width	70 mm
Article height	24 mm
Article net weight	50 g
Housing material	Aluminum
Color housing	White

## Logistic Data

Packaging length	8 cm
Packaging width	6 cm
Packaging height	11.5 cm
Packaging gross weight	90 g
EAN Product	8720246201437
Packaging paper material weight	35 g
Packaging plastic material weight	3 g
Innerbox quantity	10
Master carton length	37 cm
Master carton width	36 cm
Master carton height	46 cm
CBM master carton	0.061272 m <sup>3</sup>
Master carton quantity	100
Master carton gross weight	10.7 kg
Master carton paper material weight	4160 g
Master carton plastic material weight	300 g

Country of Origin

CN

HS Code

8536508090

View on the website: [www.shada.nl/p/0190011\\_01](http://www.shada.nl/p/0190011_01)