



0190112 Wall Sensor - PIR 180° IP54 - White

- Automatic switch-off and the timer restarts when new motion is detected
- Compact design suitable for indoor and outdoor use
- Equipped with an adjustable motion and daylight sensor

LED's light

With this sensor you will never have to struggle in the dark again to find the right key, while balancing an arm full of groceries. The sensor enables you to add motion detection to your outdoor lights as well as indoor lights. Making sure that the lights turn on once movement is detected at night.

Another advantage of an outdoor light equipped with a sensor, is improved home security. Burglars will be deterred by the sudden light.

The sensor can be installed to walls. You can set the detection field using the adjustable detector head. The time settings for switching the lights off are adjustable to your personal preferences. If there is a second detection within the set time range, the time settings are automatically restarted by the built-in time delay ability.

The sensor is splash waterproof and has a wide detection angle.

Available in white and black.

General

Brand	LED's light
Collection	Functional
Manual language	English, French, German, Spanish, Dutch
PLC Status	Active
Warranty	2-Year

Electrical

Switching capacity	Incandescent: 2000 W LED : 1000W
Power consumption	0.5 W
Input voltage.	220 — 240 V
Voltage type	AC
Input frequency	50/60 Hz
Input current.	10000 — 10000 mA
Safety class	II
Standby power	0.5 W
Inrush current	500A

Performance

IP Rating	IP54
Operating Temperature	-20 — 40 °C
Max. load LED (VA)	1000 VA
Max. load INC/HAL (W)	2000 W
Energy class (EU 2019/2015)	Not required

Mechanical

Article length	77 mm
Article width	55 mm
Article height	80 mm
Article net weight	91 g
Housing material	Acrylonitrile butadiene styrene (ABS)
Color housing	White
Mounting type	Wall

Sensor

Type of sensor	PIR
Motion speed detection	0.6 — 1.6 m/s
Sensitivity of the natural light sensor	10 — 2000 lx
Holding time	10 — 420 s
Installation height	1.8 — 2.5 m
Maximum detection angle	180 °
Detection range on typical installation height	1 — 12 m

Logistic Data

Packaging length	8 cm
Packaging width	6 cm
Packaging height	12.5 cm
Packaging gross weight	124 g
EAN Product	8720604303728
Packaging paper material weight	29 g
Packaging plastic material weight	1 g
Master carton length	42 cm
Master carton width	35 cm
Master carton height	21 cm
CBM master carton	0.03087 m ³
Master carton quantity	50
Master carton gross weight	6.7 kg
Master carton paper material weight	1934 g
Master carton plastic material weight	31 g
Country of Origin	CN
HS Code	8531103000

View on the website: www.shada.nl/p/0190112