



0230099 Floodlight - 1000W 155000lm 6000K IP66 - Lumileds(Philips) LED - Inventronics Driver - Black

- Protected against dust and high pressure jets of water
- Highly shock resistant (IK10)
- Modular design

LED's light PRO

This powerful floodlight effortlessly illuminates construction sites, warehouses and other large areas. The corrosion proof aluminum housing protects the light from dust and waterjets (IP66) and makes it vandalism proof (IK10). The light can be rotated to adjust the light output to where it's needed most. There are two handles that allow for easy transportation and installation.

This floodlight emits a powerful (155.000 lumen) daylight white light (6000K), in a narrow beam angle of 30°. This permits the light output to remain powerful and consistent at large heights, ideal for cranes on construction sites. The floodlight is powered by the included 25 m long H07RN-F 3G 1.5mm² connection cable. It utilizes a modular design and premium quality components to maximize the lifespan and cost-efficiency. The LED chips are Philips Lumileds and for the drivers Inventronics is used. This floodlight only consumes 1000W to equal the performance of 2000W HQI floodlights.

General

| | |
|-----------------|---|
| Brand | LED's light Pro |
| Collection | Functional |
| Manual language | English, French, German, Spanish, Dutch |
| Package content | Multi language manual |
| PLC Status | Active |
| Warranty | 5-Year |

Lighting

| | |
|--|-----------------------|
| Total lumens | 155000 lm |
| Useful lumens | 139500 lm |
| Adjustable luminous flux | Continuously variable |
| Lamp efficacy | 155 |
| Light sharing | Symmetric |
| Color temperature | 6000 K |
| Color description | Cool white |
| Color rendering index | 70 |
| Color consistency (McAdam Ellipse) | SDCM6 |
| Beam angle | 30 ° |
| Light distribution | Direct Symmetric |
| Photobiological safety according to EN 62471 | RG1 |
| Flicker-free | Yes |

Electrical

| | |
|-------------------|--------------------|
| Power consumption | 1000 W |
| Input voltage. | 220 — 240 V |
| Voltage type | AC |
| Input frequency | 50/60 Hz |
| Input current. | 4470 — 4470 mA |
| Safety class | I |
| Control gear type | Isolated driver |
| Type of dimming | 1-10V |
| LED chip type | SMD 5050 |
| LED chip brand | Lumileds (Philips) |
| LED chip quantity | 448 |

Power Supply

| | |
|-----------------------|--------------|
| Brand of power supply | Inventronics |
|-----------------------|--------------|

Performance

| | |
|---------------------------------|-------------|
| IP Rating | IP66 |
| Impact strength | IK10 |
| Rough service | Yes |
| Rated life time L70/B50 at 25 C | 128000 h |
| Rated life time L70/B10 at 25 C | 119000 h |
| Rated life time L80/B50 at 25 C | 81000 h |
| Rated life time L80/B10 at 25 C | 75000 h |
| Rated life time L90/B50 at 25 C | 39000 h |
| Rated life time L90/B10 at 25 C | 36000 h |
| Operating Temperature | -30 — 50 °C |
| Energy class (EU 2019/2015) | C |

Mechanical

| | |
|--------------------|--------------------------------|
| With light source | No |
| Article length | 560 mm |
| Article width | 540 mm |
| Article height | 200 mm |
| Article net weight | 26660 g |
| Housing material | Aluminum |
| Color housing | Black |
| Diffuser material | Polycarbonate (PC) |
| Diffuser finishing | Clear |
| Cable type | H07 RN-F 3G*1.5mm ² |
| Cable length | 2500 cm |
| Lamp type | LED exchangeable |
| Mounting type | Surface, Wall |

Logistic Data

| | |
|----------------------|-------------------------|
| EAN Product | 8720604304022 |
| Master carton length | 63 cm |
| Master carton width | 62 cm |
| Master carton height | 28 cm |
| CBM master carton | 0.109368 m ³ |

| | |
|---------------------------------------|------------|
| Master carton quantity | 1 |
| Master carton gross weight | 29.5 kg |
| Master carton paper material weight | 2195 g |
| Master carton plastic material weight | 536 g |
| Country of Origin | CN |
| HS Code | 9405421000 |

View on the website: www.shada.nl/p/0230099