






0300743 Battery pack- 22V IP65 IK05 - Lithium-Ion Battery

- Complement of article 300740 and 310740
- Battery indicator
- Dimmable

Create a mobile light using the battery pack.

The battery pack complements our worklight (Article No. 300740).

The battery has a convenient battery indicator, showing how much battery is left. In addition, the lamp can be dimmed via the battery and there is no external driver necessary.

LED's work

General

Brand	LED's work
Collection	Functional
PLC Status	Active

Electrical

Input voltage.	100 — 240 V
Voltage type	DC
Input frequency	50/60 Hz
Power factor	0.9
Input current.	1200 — 1200 mA
Safety class	II
Type of dimming	Button dimming
Total harmonic distortion (THD)	20

Power Supply

Input voltage power supply	null — null V
Output power supply	43.8 W
Output voltage power supply	12.5 — 12.5 VDC
Output current power supply	3500 mA

Performance

IP Rating	IP65
Impact strength	IK05
Operating Temperature	-5 — 40 °C

Mechanical

With light source	No
Article length	330 mm
Article width	160 mm
Article height	140 mm
Article net weight	2000 g
Housing material	Polyamide / Nylon (PA), Polycarbonate (PC)
Color housing	Black
Cable type	H05RN-F 2X1.0 mm^2
Cable length	3 cm
Cable color	Black
Plug type	Contour plug

Battery

NL subcategory	Packs
NL usage klass	P
Stibat code	B210035540
Stiftung Batterien (GRS) code	1028314453
Technology	Lithium-ion
Capacity	7500 mAh
Energy	167 Wh
Run time	1.5 h
Charging time	5 h
Weight	1000 g

Logistic Data

Packaging length	17 cm
Packaging width	20 cm
Packaging height	36 cm
Packaging gross weight	3126 g
EAN Product	8719323788558
Packaging paper material weight	260 g
Packaging plastic material weight	12 g
Master carton length	42 cm
Master carton width	38 cm
Master carton height	20 cm
CBM master carton	0.03192 m^3
Master carton quantity	2
Master carton gross weight	6.9 kg
Master carton paper material weight	1154 g
Master carton plastic material weight	24 g
Country of Origin	CN
HS Code	8506509090

View on the website: www.shada.nl/p/0300743