



## 0300810 Work Light - 30W 3200lm 5000K IP54 - Rough service

- Anti-glare cover
- Rough service tested
- Dust tight and waterjet protected

**LED's work**

The work light is perfect for places where a mobile and bright light source is needed, such as on construction sites, during installation work, in workshops or in workplaces. For hobby craftsmen as well as professionals.

The LED work light has a modern and robust ABS housing and is equipped with protective plastic corners and a convenient ergonomically shaped handle. The lamp is collapsible and has a five-meter-long cable, meaning that it can easily be moved around the room.

The light emits a cool white light. Furthermore, the light has a high impact resistance and is rough service tested, making it perfect for use on construction sites. The lamp is highly dust tight and splash waterproof.

F

### General

Brand	LED's work
Collection	Functional
PLC Status	Active
Warranty	2-Year

### Lighting

Total lumens	3200 lm
--------------	---------

Useful lumens	3200 lm
Adjustable color temperature	No
Lamp efficacy	107
Light sharing	Symmetric
Color temperature	5000 K
Color description	Cool white
Color rendering index	80
Color consistency [McAdam Ellipse]	SDCM6
Beam angle	110 °
Flicker-free	Yes

### [Smart] Dimming and Switching

Max. load socket[s]	3000 W
Number of CEE socket outlets	1 pcs

### Electrical

Power consumption	30 W
Input voltage.	220 — 240 V
Voltage type	AC
Input frequency	50/60 Hz
Power factor	0.97
Input current.	145 — 145 mA
Safety class	I
Control gear type	Isolated driver
Control gear mounting	Built-in
Type of dimming	Not dimmable
LED chip type	SMD 2835
LED chip brand	Sanan
LED chip quantity	140

### Power Supply

Brand of power supply	Lifud
-----------------------	-------

### Performance

IP Rating	IP54
Impact strength	IK08

Rough service	Yes
Rated life time L70/B50 at 25 C	50000 h
Operating Temperature	-25 — 40 °C
Energy class (EU 874/2012)	A+
Energy class (EU 2019/2015)	F

## Mechanical

With light source	No
Article length	291 mm
Article width	110 mm
Article height	253 mm
Article net weight	2300 g
Housing material	Acrylonitrile butadiene styrene (ABS)
Color housing	Black
Diffuser material	Polycarbonate (PC)
Diffuser finishing	Opal
Cable type	H07RN-F 3G1.5 mm <sup>2</sup>
Cable length	500 cm
Cable color	Black
Plug type	VDE plug
Lamp socket	N/A
Lamp type	LED not exchangeable

## Logistic Data

Packaging length	30 cm
Packaging width	12.5 cm
Packaging height	26.5 cm
Packaging gross weight	2540 g
EAN Product	8719323789555
Packaging paper material weight	204 g
Packaging plastic material weight	6 g
Master carton length	65 cm
Master carton width	32 cm
Master carton height	28 cm
CBM master carton	0.05824 m <sup>3</sup>
Master carton quantity	5
Master carton gross weight	13.3 kg
Master carton paper material weight	1598 g
Master carton plastic material weight	30 g

Country of Origin

CN

HS Code

9405421000

View on the website: [www.shada.nl/p/0300810](http://www.shada.nl/p/0300810)