



0300812 Work Light - 60W 6500lm 5000K IP54 - Rough service

- Extra socket for connecting tools and devices
- Rough service tested
- Dust tight and waterjet protected

The work light is perfect for places where a mobile and bright light source is needed, such as on construction sites, during installation work, in workshops or in workplaces. For hobby craftsmen as well as professionals.

The LED work light has a modern and robust ABS housing and is equipped with protective plastic corners and a convenient ergonomically shaped handle. The lamp is collapsible and has a five-meter-long cable, meaning that it can easily be moved around the room.

LED's work

The light emits a cool white light. Furthermore, the light is perfect for construction sites due to its high impact resistance. Furthermore, the light has a high impact resistance and is rough service tested, making it perfect for use on construction sites. The lamp is highly dust tight and splash waterproof.

In addition, the light includes an external socket for connecting tools or other devices.

F

General

Brand	LED's work
Collection	Functional
PLC Status	Active
Warranty	2-Year

Lighting

Total lumens	6500 lm
Useful lumens	6500 lm
Lamp efficacy	108
Light sharing	Symmetric
Color temperature	5000 K
Color description	Cool white
Color rendering index	80
Color consistency (McAdam Ellipse)	SDCM6
Beam angle	100 °
Flicker-free	Yes

[Smart] Dimming and Switching

Max. load socket[s]	3000 W
Number of CEE socket outlets	2 pcs

Electrical

Power consumption	60 W
Input voltage.	220 — 240 V
Voltage type	AC
Input frequency	50/60 Hz
Power factor	0.9
Input current.	270 — 270 mA
Safety class	I
Control gear type	Isolated driver
Control gear mounting	Built-in
Type of dimming	Not dimmable
LED chip type	SMD 2835
LED chip brand	Sanan
LED chip quantity	280

Power Supply

Brand of power supply	Lifud
-----------------------	-------

Performance

IP Rating	IP54
Impact strength	IK08
Rough service	Yes
Rated life time L70/B50 at 25 C	50000 h
Operating Temperature	-25 — 40 °C
Energy class (EU 2019/2015)	F

Mechanical

With light source	No
Article length	389 mm
Article width	100 mm
Article height	342 mm
Article net weight	2900 g
Housing material	Acrylonitrile butadiene styrene (ABS)
Color housing	Yellow
Diffuser material	Polycarbonate (PC)
Diffuser finishing	Opal
Cable type	H07RN-F 3G1.5 mm ²
Cable length	500 cm
Cable color	Black
Plug type	Hybrid plug
Lamp socket	N/A
Lamp type	LED not exchangeable

Logistic Data

Packaging length	40 cm
Packaging width	11 cm
Packaging height	35 cm
Packaging gross weight	3735 g
EAN Product	8719323789562
Packaging paper material weight	334 g
Packaging plastic material weight	7 g
Master carton length	42 cm
Master carton width	36 cm
Master carton height	37 cm
CBM master carton	0.055944 m ³
Master carton quantity	3

Master carton gross weight	11.8 kg
Master carton paper material weight	1554 g
Master carton plastic material weight	21 g
Country of Origin	CN
HS Code	9405421000

View on the website: www.shada.nl/p/0300812