



0310740 Work Light - 120W 13500lm 5000K IP65 - Rough service

- Separately movable LEDs
- Dust tight and waterjet protected
- Highly shock resistant

The Novalight provides you with 360-degree LED light and the different LEDs can be moved separately, opening up a wide range of illumination possibilities. Perfect for places where bright, flexible, and adjustable light is needed, e.g., construction sites and workplaces.

The LEDs emit a neutral white light, and the telescope tripod is of a high quality and adjustable in height.

The light is protected against waterjets and dust tight and therefore well suited for outdoor use as well. In addition, the lamp is highly shock resistant.

The Novalight is dimmable using a dimmer (Art. No. 300744) and is easy to store when not in use.

LED's work

E

General

Brand	LED's work
Collection	Functional
Manual language	Dutch, English, French, German, Spanish
Package content	Multi language manual, Tripod, External power supply
PLC Status	No longer available
Warranty	2-Year

Lighting

Total lumens	13500 lm
Useful lumens	13500 lm
Lamp efficacy	113
Color temperature	5000 K
Color description	Neutral white
Color rendering index	80
Color consistency (McAdam Ellipse)	SDCM6
Beam angle	145 °

Electrical

Power consumption	120 W
Input voltage.	220 — 240 V
Voltage type	AC
Input frequency	50/60 Hz
Power factor	0.9
Input current.	520 — 520 mA
Safety class	I
Control gear type	Non-isolated driver
Control gear mounting	Built-in
LED chip type	SMD 2835
LED chip brand	Everlight
LED chip quantity	360

Performance

IP Rating	IP65
Impact strength	IK08
Rough service	Yes
Rated life time L70/B50 at 25 C	35000 h
Operating Temperature	-20 — 45 °C
Energy class (EU 2019/2015)	E

Mechanical

With light source	No
Article length	125 mm
Article height	2270 mm
Article net weight	6600 g

Housing material	Aluminum
Color housing	Black
Diffuser material	Polycarbonate (PC)
Diffuser finishing	Opal
Cable type	H07RN-F 3G1.0 mm ²
Cable length	950 cm
Cable color	Black
Plug type	Hybrid plug
Lamp socket	N/A
Lamp type	LED exchangeable

Logistic Data

Tripod packaging length	112 cm
Tripod packaging height	18 cm
Tripod packaging width	17 cm
Tripod packaging weight	5 kg
Packaging length	27 cm
Packaging width	23.5 cm
Packaging height	53 cm
Packaging gross weight	7215 g
EAN Product	8720604301809
Packaging paper material weight	510 g
Packaging plastic material weight	105 g
Master carton length	28 cm
Master carton width	25 cm
Master carton height	55 cm
CBM master carton	0.0385 m ³
Master carton quantity	1
Master carton gross weight	7.69 kg
Master carton paper material weight	985 g
Master carton plastic material weight	105 g
EU pallet quantity	12
Country of Origin	CN
HS Code	9405421000

View on the website: www.shada.nl/p/0310740