



2400110 LED TL Luminaire with Tube - 1x9W 60cm 900lm 4000K IP65

- 105 lm/w
- Protected against dust and low pressure jets of water
- Long lifespan due to interchangeable tube

Illuminate rooms and spaces with the LED TL Luminaire with tube. Ideal for workplaces, garages, sheds, basements and smaller warehouses.

The luminaire is dust tight and against waterjets protected. The luminaire comes with a tube that is highly efficient and emits a neutral white light that is flicker-free.

The tube is interchangeable, which means that the lifespan of the luminaire is long, since only the tube needs to be replaced.

LED's light Basic

E

General

Brand	LED's light Basic
Collection	Functional
PLC Status	Phase out
Warranty	2-Year

Lighting

Luminous efficacy	100 lm/W
Total lumens	900 lm
Adjustable luminous flux	No
Adjustable color temperature	No
Lamp efficacy	100
Light sharing	Symmetric
Equivalent light output	18 W
Color temperature	4000 K
Color description	Neutral white
Color rendering index	80
Adjustable beam angle	No
Color consistency (McAdam Ellipse)	SDCM3
Beam angle	220 °
Light distribution	Direct Symmetric
Flicker-free	Yes

Electrical

Type of control gear	LED operating device voltage-controlled
Power consumption	9 W
Input voltage.	220 — 240 V
Voltage type	AC
Input frequency	50/60 Hz
Power factor	0.5
Input current.	75 — 75 mA
Safety class	II
Control gear type	IC constant current driver
Control gear mounting	On PCB
Type of dimming	Not dimmable
Glow wire test	650 °C
LED chip type	SMD 3030
LED chip brand	Epistar
LED chip quantity	44

Power Supply

Brand of power supply	OEM
-----------------------	-----

Performance

IP Rating	IP65
Impact strength	IK08
Rated life time L70/B50 at 25 C	25000 h
Rated life time L80/B50 at 25 C	25000 h
Luminaire with D mark	No
Operating Temperature	-15 — 45 °C
Energy class (EU 874/2012)	A+
Energy class (EU 2019/2015)	E

Mechanical

With light source	No
Suitable for number of lamps	1
Light outlet	Direct
Article length	685 mm
Article width	65 mm
Article height	60 mm
Article net weight	410 g
Color housing	Grey
Diffuser material	Polycarbonate (PC)
Diffuser finishing	Opal
Type of wiring	Ending
Type of gland	M16 Plastic
Lamp socket	G13
Lamp holder	T8
Lamp type	LED exchangeable
Connection type	Screw connection
Mounting type	Ceiling

Logistic Data

Packaging length	70 cm
Packaging width	7 cm
Packaging height	6 cm
Packaging gross weight	574 g
EAN Product	8720246202557
Packaging paper material weight	117 g
Packaging plastic material weight	9 g
Inner carton length	31 cm

Inner carton width	15 cm
Inner carton height	13 cm
Innerbox quantity	4
Inner carton gross weight	2.6 kg
Master carton length	73 cm
Master carton width	15 cm
Master carton height	32 cm
CBM master carton	0.03504 m ³
Master carton quantity	8
Master carton gross weight	5.6 kg
Master carton paper material weight	1964 g
Master carton plastic material weight	72 g
Country of Origin	CN
HS Code	9405114090

View on the website: www.shada.nl/p/2400110