



## 2400111 LED TL Luminaire with Tube - 2x9W 60cm 1800lm 4000K IP65

- 105 lm/w
- Protected against dust and low pressure jets of water
- Long lifespan due to interchangeable tube

Illuminate rooms and spaces with the LED TL Luminaire with tube. Ideal for workplaces, garages, sheds, basements and smaller warehouses.

The luminaire is dust tight and against waterjets protected. The luminaire comes with two tubes that are highly efficient and emit a neutral white light that is flicker-free.

The tubes are interchangeable, which means that the lifespan of the luminaire is long, since only the tubes need to be replaced.

**LED's light Basic**

E

### General

|            |                     |
|------------|---------------------|
| Brand      | LED's light Basic   |
| Collection | Functional          |
| PLC Status | No longer available |
| Warranty   | 2-Year              |

## Lighting

|                                    |               |
|------------------------------------|---------------|
| Luminous efficacy                  | 100 lm/W      |
| Total lumens                       | 1800 lm       |
| Useful lumens                      | 1080 lm       |
| Adjustable luminous flux           | No            |
| Adjustable color temperature       | No            |
| Lamp efficacy                      | 100           |
| Light sharing                      | Symmetric     |
| Equivalent light output            | 36 W          |
| Color temperature                  | 4000 K        |
| Color description                  | Neutral white |
| Color rendering index              | 80            |
| Adjustable beam angle              | No            |
| Color consistency (McAdam Ellipse) | SDCM3         |
| Beam angle                         | 220 °         |
| Flicker-free                       | Yes           |

## Electrical

|                       |   |
|-----------------------|---|
| Type of control gear  | LED operating device voltage-controlled |
| Power consumption     | 18 W                                    |
| Input voltage.        | 220 — 240 V                             |
| Voltage type          | AC                                      |
| Input frequency       | 50/60 Hz                                |
| Power factor          | 0.9                                     |
| Input current.        | 75 — 75 mA                              |
| Safety class          | II                                      |
| Control gear type     | IC constant current driver              |
| Control gear mounting | On PCB                                  |
| Type of dimming       | Not dimmable                            |
| Glow wire test        | 650 °C                                  |
| LED chip type         | SMD 3030                                |
| LED chip brand        | Epistar                                 |
| LED chip quantity     | 88                                      |

## Power Supply

|                       |     |
|-----------------------|-----|
| Brand of power supply | OEM |
|-----------------------|-----|

## Performance

|                                 |             |
|---------------------------------|-------------|
| IP Rating                       | IP65        |
| Impact strength                 | IK08        |
| Rated life time L70/B50 at 25 C | 25000 h     |
| Rated life time L80/B50 at 25 C | 25000 h     |
| Luminaire with D mark           | No          |
| Operating Temperature           | -15 — 45 °C |
| Energy class (EU 874/2012)      | A+          |
| Energy class (EU 2019/2015)     | E           |

## Mechanical

|                              |                    |
|------------------------------|--------------------|
| With light source            | No                 |
| Suitable for number of lamps | 2                  |
| Light outlet                 | Direct             |
| Article length               | 670 mm             |
| Article width                | 110 mm             |
| Article height               | 52 mm              |
| Article net weight           | 720 g              |
| Color housing                | Grey               |
| Diffuser material            | Polycarbonate (PC) |
| Diffuser finishing           | Opal               |
| Type of wiring               | Ending             |
| Type of gland                | M16 Plastic        |
| Lamp socket                  | G13                |
| Lamp holder                  | T8                 |
| Lamp type                    | LED exchangeable   |
| Connection type              | Screw connection   |
| Mounting type                | Ceiling            |

## Logistic Data

|                                   |               |
|-----------------------------------|---------------|
| Packaging length                  | 70.5 cm       |
| Packaging width                   | 11.5 cm       |
| Packaging height                  | 6 cm          |
| Packaging gross weight            | 783 g         |
| EAN Product                       | 8720246202564 |
| Packaging paper material weight   | 50 g          |
| Packaging plastic material weight | 13 g          |
| Master carton length              | 72 cm         |

|                                       |                        |
|---------------------------------------|------------------------|
| Master carton width                   | 24 cm                  |
| Master carton height                  | 20 cm                  |
| CBM master carton                     | 0.03456 m <sup>3</sup> |
| Master carton quantity                | 6                      |
| Master carton gross weight            | 5.16 kg                |
| Master carton paper material weight   | 960 g                  |
| Master carton plastic material weight | 120 g                  |
| Country of Origin                     | CN                     |
| HS Code                               | 9405114090             |

View on the website: [www.shada.nl/p/2400111](http://www.shada.nl/p/2400111)