

2400115 LED TL Luminaire with Tube - 2x22W 150cm 4620lm 4000K IP65

- 105 lm/w
- Protected against dust and low pressure jets of water
- Long lifespan due to interchangeable tube

The LED TL Luminaire with tube is perfect for workplaces, garages, sheds and smaller warehouses.

The luminaire is dust tight, protected against waterjets and highly impact resistant. In addition, the lamp comes with two tubes that are highly efficient.

The tubes are interchangeable, which means that the lifespan of the luminaire is long, since only the tubes need to be replaced. The tubes emit a neutral white light.

LED's light Basic

F

General

Brand	LED's light Basic
Collection	Functional
Manual language	Dutch, English, French, German, Spanish
Package content	Multi language manual
PLC Status	Phase out
Warranty	2-Year

Lighting

Total lumens	4620 lm
Lamp efficacy	105
Color temperature	4000 K
Color description	Neutral white
Color rendering index	80
Color consistency (McAdam Ellipse)	SDCM6
Beam angle	200 °
Flicker-free	Yes

Electrical

Power consumption	44 W
Input voltage.	220 — 240 V
Voltage type	AC

Input frequency	50/60 Hz
Power factor	0.6
Input current.	320 — 320 mA
Safety class	II
Control gear type	Driver on board
Type of dimming	Not dimmable
LED chip type	SMD 2835
LED chip quantity	240

Performance

IP Rating	IP65
Impact strength	IK03
Rated life time L70/B50 at 25 C	25000 h
Operating Temperature	-20 — 45 °C
Energy class (EU 2019/2015)	F

Mechanical

With light source	No
Suitable for number of lamps	2
Article length	1590 mm
Article width	101 mm
Article height	57 mm
Article net weight	1550 g
Housing material	Acrylonitrile butadiene styrene (ABS)
Color housing	Grey
Diffuser material	Polycarbonate (PC)
Diffuser finishing	Clear
Lamp socket	G13
Lamp holder	G13
Lamp type	LED exchangeable
Mounting type	Ceiling, Surface, Wall

Logistic Data

Packaging length	0 cm
Packaging width	0 cm
Packaging height	0 cm
Packaging gross weight	0 g



EAN Product	8720604304855
Master carton quantity	6
HS Code	9405114090

View on the website: www.shada.nl/p/2400115